

# VERTI-cutter

<b>Model</b>	<b>VC-60</b>
<b>Working Width</b>	<b>54" Blade to Blade</b>
<b>Blades</b>	<b>(28) 10GA/12 Point 12" Diameter hardened Blades</b>
<b>Blade Spacing</b>	<b>2"</b>
<b>Blade Shaft</b>	<b>1 5/8" Hex Stress Proof Shaft</b>
<b>Blade Shaft Rotation</b>	<b>Forward</b>
<b>Blade Depth</b>	<b>1/8" - 1 1/2"</b>
<b>Blade Depth Adjustment</b>	<b>Detent Pins on Skids 3/16" Increments</b>
<b>Hitch</b>	<b>Patented 3-PT. CAT. 1 Trailing Hitch</b>
<b>Drive</b>	<b>540 PTO Gearbox, (5) BX Belts to Blade Shaft</b>
<b>Required Horse Power</b>	<b>25 to 45 HP (Varies by Cutting Depth)</b>
<b>Frame</b>	<b>All Welded Steel Construction</b>
<b>Weight</b>	<b>755 lbs.</b>
<b>Dimensions</b>	<b>70" Width, 46" Length, 41" High</b>
<b>Gearbox</b>	<b>Heavy Duty 42 HP (31KW)</b>

