

KESMAC 2150 SOD HARVESTER

SOD HARVESTER



- Pivoting one piece cutter head and conveyor frame, with hydraulic depth control, floats for uniform & reliable sod thickness
- Fits [New Holland T4020](#) and [John Deere 5065E](#) tractor configurations, 2WD & 4WD
- Conveniently stored weights can be added to cutter head to adapt to various conditions
- Joystick controls all key functions: auto steer, hydraulic depth control (also at stackers station), cutter and conveyor
- Main beam forward design for better weight distribution and reduced front counter weights
- Ergonomically designed operator station with good visibility & heavy duty wrap around fenders and platform
- Easy entry with rear piling door for quick service
- Full canopy with flashing signal and halogen work lights
- Well balanced, short overall length for great maneuverability
- Low profile conveyor mat with long life tri-urethane sprockets on UHMW polyethylene slides
- Conveyor lift arm cylinder lock & fender safety grab rail

STANDARD TRACTOR	
TRACTOR MODEL	New Holland T4020 Diesel
HORSE POWER	64 (Gross) 50 PTO
TRANSMISSION	8 x 8 Synchro Command Power Shuttle optional
TRACTION	2 wheel drive (4 wheel drive option)
STEERING	Hydro Power
TIRES	Front. 11L - 15 Rear 19.5 x 24
WEIGHT (Tractor)	4665 lbs (2115 kg)

Width of cut	16" (406mm) 18" (457mm) 21" (533mm) 24" (610mm)
Length of cut	24" (610mm) to 100" (2540mm)
Thickness of Cut (With Hydraulic Control & Remote Switch)	Up to 2 1/4" (57mm)
Performance	1500 Rolls (1260 M) per hour
Controls	Joystick for all main functions
Cutter/Conveyor Drives	Hydraulic
Cutting Blades	One Piece or 3 pc Blade
Conveyor & Roll Up	Rubber belt in STD or low profile or Mintex
Pallet Sizes	48" x 48" (1219mm x 1219mm) Std.
Operating Dimensions	L. 176" (4470mm) W. 120" (3048mm) H. 104" (2641mm)
Construction	High strength steel weldment
Weight (Harvester)	3610 lbs. (1637 kg) (Harvester weight may vary on spec)