

# FIXED HEAD STANDARD

## TRANSPORTABLE REEL MOWER



- Delivers quality cut consistently from 1/2" to 3 1/4" in up to 6" tall grass
- Requires only 45HP tractor
- Rugged tubular frame design and high flotation for soft conditions
- Delivers outstanding cut even in wet or rainy conditions
- Follows field contours
- Easy reel and mowing height adjustment
- Heavy duty bed knife holder, with 9 counter sunk screws
- Available in 5, 6, 7, 8 and 9 bladed reels
- Open design for better clipping flow

## **Benefits**

- Scissor-like cut is better for your turf
- Light weight, less compaction
- Low horsepower required
- Mows up to 160 acres per day, 11 Gang or 130 acres per day, 9 Gang

**SPECIFICATIONS**

	<b>5 GANG</b>		<b>7 GANG</b>		<b>9 GANG</b>		<b>11 GANG</b>	
WIDTH OF CUT	11' - 6"	3505 mm	16' - 0"	4877 mm	20' - 6"	6250 mm	25' - 0"	7620 mm
HEIGHT OF CUT	1/2"-3 1/4"	13-83 mm	1/2"-3 1/4"	13-83 mm	1/2"-3 1/4"	13-83 mm	1/2"-3 1/4"	13-83 mm
WEIGHT	1847 lbs.	0843 Kg.	2860 lbs.	1297 Kg.	3120 lbs.	1415 Kg.	3778 lbs.	1714 Kg.
TRANSPORT HEIGHT	50"	1270 mm	79"	2005 mm	82" 2083 mm		106"	2692 mm
TRANSPORT WIDTH	95"	2415 mm	110"	2795 mm	112"	2845 mm	112"	2845 mm
LENGTH WITHOUT TONGUE	85"	2160 mm	85"	2160 mm	85"	2160 mm	85"	2160 mm
LENGTH WITH TONGUE	136"	3455 mm	136"	3455 mm	136"	3455 mm	136"	3455 mm
TIRES - MAIN FRAME	24 x 12.00 - 12		24 x 12.00 - 12		24 x 12.00 - 12		23 x 10.50 - 12 CASTER 15/600x6	
TIRES - WING FRAME	18 x 8.5 - 8		18 x 8.5 - 8		18 x 8.5 - 8		18 x 8.5 - 8	
DRIVE	PTO & V BELTS		PTO & V BELTS		PTO & V BELTS		PTO & V BELTS	
CUTTING REELS	7.88" DIA. x 30" 200 mm DIA.x762 mm		7.88" DIA. x 30" 200 mm DIA.x762 mm		7.88" DIA. x 30" 200 mm DIA.x762 mm		7.88" DIA. x 30" 200 mm DIA.x762 mm	