

# FIXED LEG MODEL

## TRUCK MOUNTED FORKLIFT



### Industries Shortest Overhang

- Inching Pedal
- See Through Mast
- Work Lights Front & Rear
- Adjustable Forks
- 120 inch Lift Height
- Side Shift
- Posi-Traction
- Fold in Hydraulic Stabilizers
- Full Instrumentation
- Deluxe Suspended Seat
- Operator Friendly Cockpit
- Theft/Vandalism Deterrence
- Optional 3-Wheel Brake System (Standard on 5500 Model)

## Soft Ride Hook-Up Systems

- Air Swing
- Air Slide
- Manual Slide
- Pad Mount

<b>TRUCK MOUNTED FORKLIFT SPECIFICATIONS</b>	<b>4500 Fixed &amp; Retractable</b>	<b>5000 Fixed &amp; Retractable</b>	<b>5500 Fixed Only</b>
Load Capacity at 24 in./610 mm Load Centre. Lbs./kg	4500/2041	5000/2268	5500/2494
Lift Height** in./mm	120/3048	120/3048	120/3048
Side Shift - in./mm	6/152	6/152	6/152
Tilt	8 deg. Fwd & Back	8 deg. Fwd & Back	8 deg. Fwd & Back
Weight † lbs./kg	<b>Fixed</b> 4810/2182	4850/2200	5550/2517
Width* in./mm	<b>Retractable</b> 5120/2322	5160/2341	N/A
Width* in./mm	96/2438	96/2438	96/2438
Length* in./mm. <b>Legs Ext.(FOPS Fold)</b>	96/2438	96/2438	96/2438
<b>Legs Ret. (Less Forks)</b>	45/1143	45/1143	45/1143
Height* in./mm**	<b>Mast Lowered</b> 95/2413	95/2413	95/2413
<b>Mast Raised</b>	155/3937	155/3937	155/3937
Truck Overhang* (Less Forks) in./mm	45/1143	45/1143	45/1143
Length Under Truck Platform* in./mm	0	0	0
<b>Retracted</b> (Less Forks)	<b>Fixed</b> 31/787	31/787	31/787
Minimum Turning Radius in./mm	57/1447	57/1447	57/1447
<b>Legs Extended</b>			
Tires. Selection of <b>Standard</b> Skid - Steer, Trencher or Turf Tread <b>Optional</b>	10/16.5 NHS 8 Ply 29 or 33 x 12.50 - 15 NHS 8 Ply	10/16.5 NHS 8 Ply 29 or 33 x 12.50 - 15 NHS 8 Ply	10/16.5 NHS 8 Ply 29 or 33 x 12.50 - 15 NHS 8 Ply
Engine	Kubota V 1505 Diesel. 4 Cyl.	Kubota V 1505-T Turbo Diesel 4. Cyl.	Kubota V 1505-T Turbo Diesel 4. Cyl.
Output	37.5 HP @ 3000/RPM Gross Intermittent	46.5 HP @ 3000/RPM Gross Intermittent	46.5 HP @ 3000/RPM Gross Intermittent
Max Travel Speed***	8 mph/13 kph	8 mph/13 kph	8 mph/13 kph
Drive	3 Wheel Hydrostatic	3 Wheel Hydrostatic	3 Wheel Hydrostatic
Fork Carriage	I.T.A. Class 11	I.T.A. Class 11	I.T.A. Class 11
Forks (Standard) in./mm	4x1 1/2 x 46 (102 x 38 x 1168)	4x1 1/2 x 46 (102 x 38 x 1168)	4x1 1/2 x 46 (102 x 38 x 1168)
Optional Forks	Available	Available	Available
Adjustable Forks in./mm	Standard 16/406. Mntg.	Standard 16/406. Mntg.	Standard 16/406. Mntg.
Posi-Traction, Manually Activated Hydraulic Diff. Lock	Standard	Standard	Standard
Theft/Vandalism Deterrence	Standard	Standard	Standard
Manual or Power Operated Hook-Up Kits	Available	Available	Available
Back Rest, Backup Alarm and Amber Strobe Light	Available	Available	Available
Counter Balance Weight Kit	Available	Available	Available