

# FLOATING HEAD FAIRWAY

## TRANSPORTABLE REEL MOWER



- Delivers quality cut consistently from 1/2" to 3 1/4" in up to 6" tall grass
- The floating head follows ground contours for low mowing heights
- High flotation, less compaction
- Requires low tractor horsepower
- Rugged tubular frame with open design, for better clipping flow
- Advanced reel design with easy single point adjustment
- Heavy duty bedknife holder, with 9 counter sunk screws
- Easy to operate and maintain
- Available with 5, 6, 7, 8 or 9 bladed reels

## **Benefits**

- Scissor-like cut is better for your turf
- Light weight, less compaction
- Low horsepower required
- Mows up to 160 acres per day, 11 Gang or 130 acres per day, 9 Gang

<b>SPECIFICATIONS</b>									
	<b>5 GANG</b>		<b>7 GANG</b>		<b>9 GANG</b>		<b>11 GANG</b>		
<b>WIDTH OF CUT</b>	11' - 6"	3505 mm	16' - 0"	4877 mm	20' - 6"	6250 mm	25' - 0"	7620 mm	
<b>HEIGHT OF CUT</b>	1/2"-3 1/4"	13-83 mm	1/2"-3 1/4"	13-83 mm	1/2"-3 1/4"	13-83 mm	1/2"-3 1/4"	13-83 mm	
<b>WEIGHT</b>	1972 lbs.	0895 Kg.	3035 lbs.	1377 Kg.	3345 lbs.	1518 Kg.	4710 lbs.	2136 Kg.	
<b>TRANSPORT HEIGHT</b>	58"	1270 mm	79"	2005 mm	82"	2083 mm	106"	2692 mm	
<b>TRANSPORT WIDTH</b>	96"	2415 mm	112"	2795 mm	112"	2845 mm	112"	2845 mm	
<b>LENGTH WITHOUT TONGUE</b>	85"	2160 mm	85"	2160 mm	85"	2160 mm	85"	2160 mm	
<b>LENGTH WITH TONGUE</b>	136"	3455 mm	136"	3455 mm	136"	3455 mm	136"	3455 mm	
<b>TIRES - MAIN FRAME</b>	24 x 12.00 - 12		24 x 12.00 - 12		23 x 12.50 - 12		23 x 12.50 - 12 CASTER 15/600x6		
<b>TIRES - WING FRAME</b>	18 x 8.5 - 8		18 x 8.5 - 8		18 x 8.5 - 8		18 x 8.5 - 8		
<b>DRIVE</b>	PTO & V BELTS		PTO & V BELTS		PTO & V BELTS		PTO & V BELTS		
<b>CUTTING REELS</b>	7.88" DIA. x 30" 200 mm DIA.x762 mm		7.88" DIA. x 30" 200 mm DIA.x762 mm		7.88" DIA. x 30" 200 mm DIA.x762 mm		7.88" DIA. x 30" 200 mm DIA.x762 mm		