



SUPER STAR G BUNKER RAKE

MODEL	9430 Super Star G Gear Drive
POWER	16hp (12 kW) Vanguard V twin cylinder , air cooled, gasoline Cast iron sleeves, 29.3 cu. In. displacement, electronic ignition Full pressure lubrication with oil filter. Engine mounted air cleaner and remote mounted Donaldson air intake filtration
CONFIGURATION	3-wheel tricycle configuration.
DRIVE	Torque converter drive from engine to geared transaxle
SPEED	Infinately variable (by engine speed) 0-12 mph (0-20 kph)
BRAKING	Disc braking on transaxle. Foot pedal actuated. Locking park brake
CONSTRUCTION	Heavy gauge steel tubing, hydraulically formed, electrically welded.
TIRES/WHEELS	Purchasers choice of (3) 22 x 11 - 8 knobbed sand tires, -or- (3) 22 x 11 - 8 turf tires
STEERING	Manual front wheel steering, 15" (38 cm) diameter automotive type, adjustable tilt steering wheel
CONTROLS	Foot pedal accelerator, foot pedal brake hydraulic ram for rear implement lift/lower (Optional) hydraulic ram for center mounted implements.
SEAT	Low back adjustable deluxe seat, 1 piece molded, 1/2 back support
ELECTRICAL	12 volt battery; 12 volt electric starter, side mounted Ignition switch, operator presence switch in seat.
SOUND LEVEL	82dB(A) under normal operating conditions
DIMENSIONS (Inches/m) (Length-Width-Height)	56 in (1.42m) - 74 in (1.88m) - 46 in (1.16m); Wheelbase: 40 in (1.01m) Ground Clearance 9" (23 cm) –under cultivator
WEIGHT	650 lbs (995 kg)
LIQUID CAPACITIES	Gasoline (unleaded): 5 gallons (19 liter) in high density polyethylene tank Hydraulic system oil: 5 gallons (19 liter) in high density polyethylene tank
SAFETY & CONFORMANCE	Complies with all applicable ANSI, OSHA, and European Machinery Directive standards

IMPLEMENTS

Many efficient and effective implements for constructing and maintaining sand bunkers and other areas on the golf course.

		SHIP WT.
Rear Mounted Implements		
13-298	Fan Rake for Sand Traps	36
13-319	Fan Rake Add On for 13-438 Rake Assembly	20
13-438	Sand Trap Rake Assembly	66
13-684	Brush Attachment for all rakes except 42-130, 42-026	20
42-130	84" (213 cm) Mild Steel Tournament Rake	85
42-132	72" (189 cm) Mild Steel Tournament Rake	75
42-392	84" (213 cm) Multi Brush Rake	100
42-391	72" (189 cm) Multi Brush Rake	90
Center Mounted Implements		
42-008	Sand Cultivator	20
42-340	Sand Cultivator w/Spring Tine Teeth	20
42-401	Manual lift/lower for center Implements	20
Front Mounted Implements		
42-011	40" (102 cm) Front Mounted Plow (aluminum blade)	65