



SUPER STAR BUNKER RAKE

MODELS	42-000F 42-000E 42-001D 42-400A	Super Star SP 3-WD Series/Parallel Traction Drive Super Star 3-WD Classic Parallel Traction Drive Super Star 2-WD Super Star LE 2-WD
POWER	16hp (12 kW) Vanguard V twin cylinder , air cooled, gasoline Cast iron sleeves, 29.3 cu. In. displacement, electronic ignition Full pressure lubrication with oil filter. Engine mounted air cleaner and remote mounted Donaldson air intake filtration	
CONFIGURATION	3-wheel tricycle configuration, rear engine placement	
DRIVE	Direct multi v-belt drive (with manual clutch for easy cold weather starting) Hydrostatic variable displacement pump to two hydraulic drive motors on rear wheels (Model 42-001D 2-wheel drive) or to two hydraulic drive motors on rear wheels and one hydraulic motor on front wheel (Model 42-000F). Series-Parallel traction drive to all 3 wheels. Hydraulic oil system cooler with engine driven air flow.	
SPEED	0-12 mph (0-20 kph) Both 2-Wheel and 3-Wheel Drive Units	
BRAKING	Dynamic braking through the hydrostatic transmission Hand operated, disc type park/emergency brake	
CONSTRUCTION	Heavy gauge square steel tubing, hydraulically formed, electrically welded.	
TIRES/WHEELS	Purchasers choice of (3) 22 x 11 - 10 knobbed sand tires, -or- (3) 23-10.50 x 22 turf tires	
STEERING	Manual front wheel steering, 15" (38 cm) diameter automotive type, adjustable tilt steering wheel	
CONTROLS	Foot pedal for forward and rear operation of hydraulic system "Pro-Pedal" system connects engine throttle to hydraulic demand (Engine speed increases as hydraulic system demand increases) "Speed Boss" pre-set speed control system on hydrostatic transmission. Hydraulic engage/disengage levers control rear mounted and center mounted implements.	
SEAT	Deluxe padded, vinyl covered seat, 1 piece molded, High back support, adjustable operator position	
ELECTRICAL	12 volt battery; 12 volt electric starter, side mounted Ignition switch, operator presence switch in seat.	
SOUND LEVEL	87dB(A) under normal operating conditions	
DIMENSIONS (Inches/m) (Length-Width-Height)	64 in (1.63m) - 57 in (1.45m) - 47 in (1.19m); Wheelbase: 41 in (1.04m) Ground Clearance 9 in (23 cm) - under cultivator	
WEIGHT	950 lbs (451 kg)	

LIQUID CAPACITIES	Gasoline (unleaded): 5 gallons (19 liter) in high density polyethylene tank Hydraulic system oil: 5 gallons (19 liter) in high density polyethylene tank
SAFETY & CONFORMANCE	Complies with all applicable ANSI, OSHA, and European Machinery Directive standards
OPTIONS	42-315 Front Light Kit; 42-800 Certified ROPS; 15-622 Weather Canopy; 42-805 Fender Kit
IMPLEMENTS	Many efficient and effective implements for constructing and maintaining sand bunkers and other areas on the golf course. Please see below.

Rear Mounted Implements

SHIP WT.

13-298Q	Fan Rake for Sand Traps	36
13-319	Fan Rake Add On for 13-438 Rake Assembly	20
13-438Q	Sand Trap Rake Assembly	66
13-684	Brush Attachment for all rakes except 42-130	20
13-740	Brush Attachment for 42-130	20
34-191Q	Box Grader	273
42-130Q	84" (213 cm) Mild Steel Tournament Rake	85
42-132Q	72" (189 cm) Mild Steel Tournament Rake	75
42-392Q	84" (213 cm) Multi Brush Rake	100
42-391Q	72" (189 cm) Multi Brush Rake	90
41-501	Typhoon Pumping System	480
43-010	Engine powered Leaf & Debris Blower	180
41-502	EarthWay [®] Spreader	50

Center Mounted Implements

42-008	Sand Cultivator	20
42-223	Adjustable Disc Edger	30
42-750	Cart Path/Sidewalk Edger	30
42-340	Sand Cultivator w/Spring Tine Teeth	20
43-130	Weed Cultivator w/ Feet	25

Front Mounted Implements

42-011	40" (102 cm) Front Mounted Plow (aluminum blade)	65
43-003	40" (102 cm) Hydraulic Plow	70
42-460	40" (102 cm) Adjustable Angle Plow	85
42-136	60" (155 cm) Front Mounted Manual Plow	75
42-490	60" (155 cm) Adjustable Angle manual Plow	100

GREEN STAR

ROLLER-BRUSH-SPIKER SYSTEM

42-550Q	Green Star Total RBS System <i>Complete Roller, Brush and Spiker & mounting frame</i>	285
42-586Q	Green Star RBS Main Frame only <i>Mounting frame</i>	50
42-581	Green Star Roller Set (3) only (Requires 42-586Q Main Frame Assembly)	85
42-585	Green Star Brush Set (3) only (Requires 42-586Q Main Frame Assembly)	20
42-582	Green Star Spiker Set (3) only (Requires 42-586Q Main Frame Assembly)	130