

# TURFCO® CR-7

TOPDRESSER & MATERIAL HANDLER



## GREATER CAPACITY WITH WIDESPIN™ TECHNOLOGY LETS YOU COVER MORE GROUND USING A SMALLER TRACTOR.



The new CR-7 topdresser and materials handler from Turfco® is designed for sports complexes with multiple fields and for completing renovation work. Utilizing WideSpin™ technology, the CR-7 assures you the most accurate spread, from light to heavy and up to 35-feet wide. An adjustable

spinner angle allows you to drive topdressing into the turf for better integration, with a total range of 17 degrees up and down. Designed to accommodate smaller equipment without sacrificing productivity, the CR-7 delivers any material quickly and easily.

### THE NEW CR-7 MAKES TOPDRESSING EVEN EASIER BY COMBINING PATENTED TECHNOLOGY WITH BUILT-IN VERSATILITY:

- > Designed for versatility, the CR-7 is ideal for topdressing, fixing washout areas, mulching, compost material, back-fill drainage trenches and for updating flowerbeds
- > Easily load and unload the 2.0 cubic yard capacity self-cleaning galvanized hopper
- > Easily access tighter areas with the optional rear-mounted cross-conveyor featuring a 180-degree swivel
- > With a seven-gallons-per-minute flow, easily handle a wide variety of wet or dry material including sand, lime, compost, stone, wood chips, soil conditioners and grass clippings
- > Patented three-position switch assure a clean application every time by turning on the attachments before the main conveyor
- > Standard 3-year warranty keeps you up and running

SPECIFICATIONS	
Model	85470
Drive	Tractor's hydraulic system powers belt and attachments
Hopper Capacity	1.8 cubic yards
Hopper	Galvanized steel
Conveyor Belt	18" wide, pebble grain surface with heavy-duty polyester cord. Single seam.
Transport Speed	Up to 15 mph empty; 8 mph loaded
Metering Gate	Full manual adjustment with curved gate
Controls	3 position, hand held switch independently operates belt and attachments. Adjustable flow control sets speed of belt and attachments. Adjustable twin spinner sets angle for broadcast top dressing up to 15 degrees up or down.
Wheels	Four 26.5 x 14-12 4-ply turf tires with walking high beam suspension
Hitch	Heavy duty pin hitch
Tractor Requirements	Minimum of 35 HP with one bank of hydraulics and 6 gpm flow.
Empty Weight	1450 lbs.
Dimensions	143" long w/o hitch x 76" wide x 64" tall
Options	Material handler conveyor with swivel; Spinners for topdressing 15' to 35' wide
Warranty	3 years parts and labor