




+++++



Mete-R-Matic Topdresser



*Anniversary
Giveaway*
REGISTER TO WIN

#1 in topdressers since 1961: Unparalleled consistency regardless of ground speed combined with a self-propelled design make the Mete-R-Matic® topdresser vital to your business. Easily maneuver across greens and other turf areas to topdress with any material including compost, sand, peat and crumb rubber. With fingertip access to controls, and designed with a powered brush and patented Chevron® topdressing belt, the Turfco Mete-R-Matic topdresser delivers the most precise spread available.

- Its light footprint is very helpful for new or refurbished greens, reducing the traffic of utility vehicles.
- Operator controls allow fingertip access to forward, reverse, brakes and throttle.
- New plastic guards with insulation for quieter operation.

Model: F15B, Product Number 85417

Engine: 5.5 HP (4.04 kW) Honda ® engine with recoil start Hopper

Capacity: 11.5 cubic feet (0.33 cubic meter), filled level at top of hopper

Spreading Width: 31-1/2" (0.8 m)Top

Dressing Speed: Up to 2.5 mph (4 km/h)

Transport Speed: Up to 2.5 mph (4 km/h)

Conveyor Belt: 34" wide composition belt with chevron surface and heavy-duty polyester cord

Metering Gate: Fine adjustment to maximum 3" (76 mm) opening

Brush: 9" (228 mm) diameter, polypropylene bristle

Controls: Throttle, traction, reverse, brake, engine on/off switch, conveyor drive and metering gate controls all within easy reach of the operator

Drive: V-belt from engine, roller chain and gear drive to conveyor, traction and brush

Wheels & Tires: Five, 13 x 6.50 x 6 rib thread turf tires

Weight: 650 lbs. (295 kg)

Shipping Weight: 750 lbs. (341 kg) Shipping

Dimensions: 79" x 48-1/2" x 35-1/2", 77.7 cu. ft. (2.01 m x 1.23 m x 0.9 m, 2.2 cubic meters)