



WideSpin™ 1530 TM Topdresser



Anniversary Giveaway
REGISTER TO WIN

Transform your four-wheel vehicle into a quality broadcast topdresser: The Turfco WideSpin 1530 TM is designed to help you achieve the best spread anywhere on your course. And with a few simple mounting brackets and connections, you can easily turn your four-wheel Cushman® Turf-Truckster®, John Deere ProGator™ or Toro® Workman® into a broadcast topdresser.

Patented WideSpin Technology allows you to switch from a light, 40-foot spread to a 15-foot heavy spread in five minutes without attachments. The spinner angle adjusts from 0-15-degree for greater control and better penetration. This unique technology, combined with a patented three-position switch, assures you that the spinners turn on before the conveyor for a clean application every time.

- Topdresses so light that it requires no dragging.
- 30 ft wide light application allows you to topdress 18 greens in 90 minutes.
- Switch from light spread to 15 ft heavy spread for after aerification in five minutes without attachments.
- Spinner angle is adjustable from 0-15° for greater control and better penetration of turf, even on windy days.
- Galvanized hopper for worry-free, rust proof durability—no paint to get sanded away.
- Patented three-position switch guarantees spinners turn on before conveyor ensuring a clean application every time.
- Trench filler attachment available.
- 19 cubic feet hopper minimizes weight on greens and turf truck.
- Now includes WideSpin

Models: WideSpin 1530 TM Truck-Mounted

- * Cushman number 85812 (includes mounting kit)
- * John Deere number 85813, requires mounting kit number 86161
- * Toro number 85813, requires mounting kit number 86160.

Hopper Capacity: 19 cubic feet (0.54 cubic meters), galvanized panels

Hopper Size:

- * Cushman model is 60" x 37" inches (1.52 x 0.94 meter) at top
- * John Deere and Toro models are 74" x 32" (1.88 x 0.81 meter) at top

Spreading Width: 15' to 30' (9.14 meters)

Spread Application: From as little as 1/32" (0.08 mm) to more than 1/4" (6.35 mm) using patented WideSpin Technology.

Topdressing Speed: Up to 5 mph (8 km/h)

Conveyor Belt: 18" (0.46 meter) wide, pebble surface composition with heavy-duty polyester cord.

Metering Gate: Full manual adjustment for LIGHTSPREAD™ and HEAVYSPREAD™ operation.

Operator Controls: Patented three-position control operates belt and spinners independently – 1530 TM only.

Drive: Trucks hydraulic system powers the belt and spinner plates.

Empty Weight: 660 lbs. (299 kg)–85811 629 lbs. (285 kg)–85183 680 lbs. (308.4 kg) – 85816 Turf Truck

Requirements:

- * Cushman: Hi-lo hydraulic accessory must be installed on truck (part # 894712 for gas or 894713 for diesel).
- * John Deere: Hydraulic auxiliary kit required; comes standard on vehicle.
- * Toro: Hi-lo hydraulic accessory must be installed on truck (part number 07228).

Optional:

- ✓ Trench-filler attachment, product number 86150
- ✓ Cross conveyor attachment, product number 86172
- ✓ Storage stand, product number 86139.