



WideSpin™ 1530 Topdresser



Designed for the most demanding applications: Get the industry's best spread anywhere on your course with the WideSpin™ 1530. Topdress 18 greens in 90 minutes with the most uniform spread in the industry. Just hook up and go, using the least amount of adjustments, you can switch from ultralight (30-ft) to ultra heavy (9-ft) applications and anything in between. The spinner angle can be adjusted from 0-15-degrees for greater control and better turf penetration. The patented three-position switch guarantees the spinners turn on before the conveyor to ensure a clean application every single time. The galvanized hopper allows for worry-free, rust proof durability with no paint to get sanded away.

- Topdresses so light that it requires no dragging.
- 30 ft wide light application allows you to topdress 18 greens in 90 minutes.
- Switch from light spread to 15 ft heavy spread for after aerification in five minutes.
- Spinner angle is adjustable from 0-15° for greater control and better penetration of turf, even on windy days.
- Galvanized hopper for worry-free, rust proof durability—no paint to get sanded away.
- Patented three-position switch guarantees spinners turn on before conveyor ensuring a clean application every time.

Model: WideSpin 1530 Tow-Behind; product number 85808

Engine: 11.0 HP (8.2 kW) Briggs® Vanguard™ with electric start

Hopper Capacity: 21 cubic feet (0.6 cubic meter), galvanized panels

Spreading Width: 15' to 30' (9.14 meters)

Spread Application: From as little as 1/32" (0.08 mm) to more than 1/4" (6.35 mm) using patented WideSpin Technology.

Topdressing Speed: Up to 8 mph (12.8 km/h)

Transport Speed: 8 mph (12.8 km/h) loaded

Conveyor Belt: 18" (0.46 meter) wide, pebble surface composition with heavy-duty polyester cord.

Metering Gate: Full manual adjustment for LIGHTSPREAD™ and HEAVYSPREAD™ operation.

Operator Controls:

- ✓ Patented three-position switch turns spinners on before conveyor with a remote throttle
- ✓ Independent spinner speed and conveyor control.

Drive: Hydraulic system powers belt and spinner plates.

Wheels: Two 26.5" x 14"-12" NHS turf tires Hitch: Heavy-duty pin hitch

Empty Weight: 1,169 lbs. (530 kg)

Optional:

- ✓ Trench-filler attachment, product number 86150
- ✓ 5th wheel hitch, product number 86138 (replaces removable spinner assembly)
- ✓ Cross conveyor attachment, product number 86172
- ✓ Hopper extension kit, product number 86175.