



## WideSpin™ 1540 TEC Topdresser



The new truck-mounted WideSpin™ 1540 TEC, featuring an easy to use electronic controller, and WideSpin 1530 TM deliver improved efficiency and greater control. A few simple mounting brackets and connections is all it takes to turn your four-wheel Cushman® Turf-Truckster®, John Deere ProGator™ or Toro® Workman® into a quality broadcast topdresser.

The industry's best spread every time: Patented WideSpin technology with a unique electronic controller, the WideSpin 1540 TEC offers the industry's greatest level of flexibility and precision available. Our specially designed twin spinners provide an unmatched 26-degree spinner angle adjustment, allowing you to spread up to 40 feet with even better turf penetration. Combined with an easy-to-use electronic controller featuring superintendent lockout, you can customize and set up to three rates to assure consistent results each time, even with different operators. Now you can do up to 95% of your applications without any mechanical adjustments. Dial in the exact program you want, from ultra light to ultra heavy and everything in between. Just set the rates using presets and superintendent lockout. When your crew goes to work, you'll get the application you want. Guaranteed.

# Set Your Program Once for a Consistent Application Every Time— it's as Easy as A-B-C



The new WideSpin™ 1540 TEC Topdresser features an easy to use electronic controller. Featuring three preset buttons, you can dial in and lock up to three customized application rates for greens, tees and approaches—ultimately allowing you to switch rates without getting out of your seat. Our new electronic controller features:

- Patented three-position switch guarantees a clean application.
- Digitally controlled spinner and belt speeds can be adjusted to your ideal rates.
- Superintendent lockout prevents tampering of your preset application rates.

## Delivers the Ultimate in Versatility and Simplicity

### BEST SPREAD

- Patented WideSpin design gives you the perfect spread with the least adjustments.
- Switches easily from light to heavy spreads and everything in between.
- 30 percent more spinner angle provides maximum versatility.

### HIGHEST CONTROL

- New electronic controller features three customizable preset buttons.
- Superintendent lockout assures you get the same spread every time you topdress.
- Instantaneously change belt and spinner speed for maximum productivity.

### GREATEST DURABILITY

- Features Turfco's industry-leading 3-year warranty.
- Unique design protects the spinner motors from debris for a longer life.
- New and improved shield makes clean-up easier than ever.

**Models:**

- \* 85816 WideSpin 1540 TEC Truck-Mounted for Cushman Turf Truckster (includes mounting kit).
- \* 85818 WideSpin 1540 TEC Truck-Mounted for JohnDeere ProGator and Toro Workman (mounting kits required)
- \* John Deere mounting kit 86180 Toro Workman mounting kit 86179.

**Hopper Capacity:**

- \* Cushman: 19 cubic feet (0.54 cubic meters)
- \* John Deere and Toro: 21 cubic feet struck level (0.59cubic meters), 25 cubic feet heaped (0.71 cubic meters).

Both models have galvanized panels

**Hopper Size:**

- \* Cushman: 60" x 37" inches (1.52 x 0.94 meter) at top.
- \* John Deere and Toro: 75" x 36" (1.9 x 0.91 meter) at top

**Spreading Width:** 9' to 40' (2.74 to 12.19 meters)

**Spread Application:** From as little as 1/32" (0.08 mm) to more than 1/4" (6.35 mm) using patented WideSpin Technology.

**Topdressing Speed:** Up to 5 mph (8 km/h)

**Conveyor Belt:** 18" (0.46 meter) wide, pebble surface composition with heavy-duty polyester cord.

**Metering Gate:** Full manual adjustment for LIGHTSPREAD™ and HEAVYSPREAD™ operation.

**Operator Controls:** Electronic control box with 3 programmable presets and lock-out capability. Patented three-position switch turns spinners on before conveyor with integrated remote throttle up/down; independent spinner speed and conveyor control.

**Drive:** Trucks hydraulic system powers the belt and spinner plates.

**Empty Weight:** 680 lbs. (308.4 kg) – 85816 730 lbs. (331.1 kg) – 85818 Turf Truck

**Requirements:**

- ✓ Cushman: Hi-lo hydraulic accessory must be installed on truck (part number 894712 for gas or 894713 for diesel).
- ✓ John Deere: Hydraulic auxiliary kit required; comes standard on vehicle.
- ✓ Toro: Hi-lo hydraulic accessory must be installed on truck (part number 07228).

**Optional:**

- ✓ Trench-filler attachment, product number 86150
- ✓ Cross conveyor attachment, product number 86172
- ✓ Storage stand, product number 86139.