

Milliken®

# Evergreen Viva™

Green Turf Paint & Divot Paint Mix

## The professional look for your athletic field

*Green Turf Colorant for dormant or discolored grasses:*

Athletic Fields ▪ Commercial/ Home Lawns  
Golf Courses ▪ Specialty Turf Applications

Evergreen is designed to cover the missing chlorophyll color of dormant or discolored grasses. Evergreen is an environmentally safe green pigment that will not harm the turf or fade from ultraviolet light. Reduced maintenance cost for winter over-seeding can be achieved by applying Evergreen to the desired color. Evergreen is recommended for use on all types of athletic fields, golf course, municipal/industrial lawns and residential lawns.

3000005087 Fr

Milliken™

Milliken & Company  
920 Milliken Road  
Spartanburg, SC 29303  
1-800-845-8502  
www.millikenturf.com

Net Contents: 2.5 Gallons (9.46 L)  
Net Weight: 21.58 Lbs (9.79 Kg)

■ PMS 576

■ Process Black

Size 6.75 x 6.75"

Milliken

# Evergreen Viva™

Green Turf Paint & Divot Paint Mix

## PRECAUTIONARY STATEMENTS (READ CAREFULLY)

- For professional use only.
- Shake well before using.
- Keep from freezing.
- Keep out reach of children.
- Apply in temperature above 40° in dry conditions
- Permanent staining will occur on non-turf areas such as side walks, various surfaces of buildings, edging, and ornamentals. Rinse immediately before drying occurs.
- Avoid application on windy days.
- Allow sufficient drying time before use of turf.
- Calibrate spray equipment to maximize the product for even turf coverage.
- Avoid over dilution of concentrate above a 1 to 20 ratio of pigment to water.

**PREPARATION:** Prior to applying Evergreen, cut turf to desired height and remove thatch if needed. Calibrate spray equipment with water to medium coarse spray. To complete the calibration, select a trial area to set the speed of the spray equipment and the amount of liquid used in the trial area. Testing a small area for desired color is recommended.

**MIXING:** Shake Evergreen container before diluting with water. Using commercial spray equipment, fill dilution tank half the desired level and start agitation. Add the correct amount of Evergreen and finish filling the mixing tank. For spot treating with handheld or back-pack tanks, add correct amount of concentrate to half filled tank, finish filling sprayer with water and shake the dilution.

**COVERAGE RATE:** An accepted turf coverage range for one gallon of Evergreen is between 3,000 to 10,000 square feet. The coverage rate will depend upon the height and texture of the turf, the speed and setting of the spray equipment, natural turf color, or color desired.

**FOR DORMANT GRASS APPLICATIONS:** Dilute one gallon of Evergreen in 10 to 15 gallons of water. Generally a cross spray

pattern on a second application will achieve more uniform turf color. For spot treatment in summer applications, place 8 to 14 ounces in one gallon of water and spray area until discolored grass is blended to the surrounding natural turf.

**FOR DIVOT MIX APPLICATIONS:** To paint divot mixture of sand, or calcined clay, combine one gallon of Evergreen with one to 3 gallons of water. Spray the divot mix while mechanically blending the components to the desired color.

## CAUTION: HEALTH HAZARD INFORMATION

Always mix in well ventilated areas. The concentrated form of this material may release ammonia vapors that could produce irritation upon contact with eyes or respiratory passages. Repeated skin contact may produce skin rashes or irritation. Wash hands thoroughly with soap and water after using, and in case of contact with eyes, flush eyes for 15 minutes with water. Seek medical attention if irritation persists. If ingestion occurs, consult physician. Do not apply contents to food stuffs or animal feeds. Be aware that clothing and shoes may be permanently stained from this product.

## STORAGE AND HANDLING

Store in original containers inaccessible to children. Triple rinse (or equivalent) container after use and disposal must be in accordance with all federal, state and local regulations.

## LIMITED WARRANTY AND DISCLAIMER

Milliken & Company warrants that this material conforms to its chemical description and is reasonably fit for the purpose stated on the label when used in accordance with directions and under normal conditions of use. Neither this warranty nor any other warranty of merchantability or fitness for a particular purpose, expressed or implied, extends to the use of this product contrary to label instructions, or under abnormal conditions not reasonably foreseeable to Milliken & Company. In no event shall Milliken & Company liability for any breach of warranty exceed the purchase price of the material as to which claim is made. Milliken & Company shall be held harmless and indemnified by the purchaser.

3000005087 Bk

■ PMS 576

■ Process Black

Size 6.75 x 6.75"